

12mm [$\frac{1}{2}$ "] GYPSUM BOARD WITH TYPE S-12 x25mm [1"] STEEL SCREWS AT 305mm [12"] O/C. PROVIDE 2 COATS OF JOINT COMPOUND TO SCREW HEADS AND TAPED JOINT

89mm [$3\frac{1}{2}$ "] GALVANIZED 20 GA STEEL STUDS AT 610mm [24"] O/C, SELF SUPPORTING AND ATTACHED TO FLOOR AND CEILING RUNNERS, IN ACCORDANCE WITH AISI SPECIFICATIONS.

50mm [2"] POLYURETHANE INSULATION WITHIN CF8i FORMS

150mm [6"] CONCRETE WALL WITHIN CF8i FORMS.

INTERIOR

EXTERIOR

100mm [4"] 200mm [$7\frac{7}{8}$ "]

PLAN VIEW

- DETAIL FOR FORMWORK ONLY
 - ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.
 100 Galcat Drive, Unit #2,
 Woodbridge, Ontario, Canada L4L 0B9
 Tel: 905-652-0001 Fax: 905-652-0002
 Toll Free: 1-877-747-9255
 Web Page: www.nuformdirect.com

**200mm [8"] CF8i WALL -
 GYPSUM WALL BOARD
 (THERMAL BARRIER)**



DRAWING NO.	A315
COPYRIGHT 2024	

SCALE:

REVISION No.:	R00
---------------	------------