

## HEADER SECTION

NO SEALANT ABOVE  
FLASHING

FLASHING INSTALLED  
AS DETAIL A092

1"  $\frac{7}{8}$ " 1 $\frac{1}{2}$ "

17

APPLY SEALANT WITH  
BACKING ROD ALL  
AROUND AT EACH SIDE  
OF LOUVRE FRAME

LOUVRE (BY OTHERS)

## OPENING

14

APPLY  $\frac{1}{4}$ " CORNER BEAD  
OF SEALANT AT TOP AND  
BOTTOM OF STARTER TO  
FLASHING AT HEADER AND  
SILL OF OPENING.

## JAMB SECTION

UNCORED CONFORM  
STARTER INSTALLED AS  
DETAIL A091

15

ANCHOR LOUVRE AS  
REQUIRED BY LOUVRE  
MANUFACTURER

## SILL SECTION

17

APPLY SEALANT WITH  
BACKING ROD ALL  
AROUND AT EACH SIDE  
OF WINDOW FRAME

FLASHING INSTALLED  
AS DETAIL A093

1"

TO SUIT  
WINDOW FRAME

- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST  
BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL  
ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.  
1 Regalcrest Court,  
Woodbridge, Ontario, Canada L4L 8P3  
Tel: 905-652-0001 Fax: 905-652-0002  
Toll Free: 1-877-747-9255  
Web Page: www.nuformdirect.com

8" CF8i WALL -  
LOUVRE BY OTHERS



DRAWING NO.

A245

COPYRIGHT 2008

SCALE:

2":1'

REVISION No.:

R00