

## HEADER SECTION

8" CF8i WALL

NO SEALANT ABOVE FLASHING

FLASHING INSTALLED AS DETAIL A092

17  
APPLY SEALANT WITH BACKING ROD ALL AROUND AT EACH SIDE OF DOOR FRAME

HOLLOW METAL DOOR AND FRAME

14

APPLY  $\frac{1}{4}$ " CORNER BEAD OF SEALANT AT TOP OF STARTER TO FLASHING AT HEADER OF OPENING.

WEATHERSTRIP

OPENING

## JAMB SECTION

UNCORED CONFORM STARTER INSTALLED AS DETAIL A090

15

INSTALL SHIMS TO CENTRE DOOR FRAME IN ROUGH OPENING

16

FASTEN FRAME WITH  $\frac{3}{8}$ "  $\phi$  x 5" FLATHEAD EXPANSION ANCHOR BOLTS. (3 PER JAMB)

ROUGH OPENING

## SILL SECTION

HOLLOW METAL DOOR

DOOR SWEEP

DOOR SILL

- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.  
1 Regalcrest Court,  
Woodbridge, Ontario, Canada L4L 8P3  
Tel: 905-652-0001 Fax: 905-652-0002  
Toll Free: 1-877-747-9255  
Web Page: www.nuformdirect.com

8" CF8i WALL -  
HOLLOW METAL DOOR  
EXTERIOR



DRAWING NO.

A125

COPYRIGHT 2008

SCALE:

2":1'

REVISION No.:

R00