

## FLASHING

N.T.S.

6

APPLY  $\frac{3}{8}$ " CONTINUOUS CORNER BEAD  $\frac{3}{8}$ " OF SEALANT AND  $\frac{3}{8}$ " CONTINUOUS FLAT BEAD OF SEALANT ON TOP OF FLASHING AT INSIDE FACE OF FLASHING.

5

$\frac{3}{8}$ " CONTINUOUS FLAT BEAD OF SEALANT ON TOP OF FLASHING AND ON INSIDE LEG OF FLASHING, AT EACH END OF FLASHING.

7

APPLY  $\frac{3}{8}$ " FLAT BEAD OF SEALANT AROUND PRE-DRILLED HOLES FOR SCREWS.

CONCRETE WALL WITH CONFORM.

## HEADER SECTION

DO NOT APPLY SEALANT ABOVE FLASHING.

16 GA GALVANIZED FLASHING WITH PREDRILLED HOLES FOR SCREWS AT CENTERLINE OF CONCRETE.

8


SECURE FLASHING WITH FLAT HEAD CONCRETE SCREWS AT 2" FROM EACH END AND 1'-1 $\frac{1}{8}$ " o/c MAX.

7

SEALANT AROUND HOLES FOR SCREWS.

6

CONTINUOUS CORNER AND FLAT BEADS OF SEALANT AT TOP OF FLASHING AT INSIDE FACE OF HEADER.



- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.  
1 Regalcrest Court,  
Woodbridge, Ontario, Canada L4L 8P3  
Tel: 905-652-0001 Fax: 905-652-0002  
Toll Free: 1-877-747-9255  
Web Page: www.nuformdirect.com

## CONFORM WALL OPENING -HEADER FLASHING



DRAWING NO.

A092

COPYRIGHT 2008

SCALE:

4":1'

REVISION No.:

R00