

FLASHING
N.T.S.

11


APPLY $\frac{3}{8}$ " FLAT BEAD OF SEALANT AROUND PRE-DRILLED HOLES FOR SCREWS.

10

APPLY $\frac{3}{8}$ " CONTINUOUS FLAT BEAD OF SEALANT ON UNDERSIDE OF FLASHING AT BOTH SIDE OF FLASHING.

9


APPLY $\frac{3}{8}$ " CONTINUOUS FLAT BEAD OF SEALANT ON UNDERSIDE OF FLASHING AT EACH END OF FLASHING.



16 GA GALVANIZED FLASHING WITH PREDRILLED HOLES FOR SCREWS AT 2" FROM INSIDE FACE OF FLASHING.

11

SEALANT AROUND HOLES FOR SCREWS.



SILL SECTION

13

APPLY $\frac{1}{4}$ " CONTINUOUS CORNER BEAD $\frac{1}{4}$ " OF SEALANT AT UNDERSIDE OF FLASHING.

12

SECURE FLASHING WITH FLAT HEAD CONCRETE SCREW AT 2" FROM EACH END AND 1'-1 $\frac{1}{8}$ " o/c MAX.

10

CONTINUOUS FLAT BEAD OF SEALANT ON UNDERSIDE OF FLASHING.

CONCRETE WALL WITH CONFORM.

- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.
1 Regalcrest Court,
Woodbridge, Ontario, Canada L4L 8P3
Tel: 905-652-0001 Fax: 905-652-0002
Toll Free: 1-877-747-9255
Web Page: www.nuformdirect.com

CONFORM WALL OPENING
-SILL FLASHING



DRAWING NO.

A093

COPYRIGHT 2008

SCALE:

4":1'

REVISION No.:

R00