

## HEADER SECTION

8" CF8i WALL

NO SEALANT ABOVE FLASHING

FLASHING INSTALLED AS DETAIL A092

1"  $7\frac{7}{8}"$   $1\frac{1}{2}"$

17

APPLY SEALANT WITH BACKING ROD ALL AROUND AT EACH SIDE OF WINDOW FRAME

WINDOW (BY OTHERS)

14

APPLY  $\frac{1}{4}"$  CORNER BEAD OF SEALANT AT TOP AND BOTTOM OF STARTER TO FLASHING AT HEADER AND SILL OF OPENING.

OPENING

## JAMB SECTION

UNCORED CONFORM STARTER INSTALLED AS DETAIL A091

15

ANCHOR WINDOW AS REQUIRED BY WINDOW MANUFACTURER

WINDOW (BY OTHERS)

## SILL SECTION

17

APPLY SEALANT WITH BACKING ROD ALL AROUND AT EACH SIDE OF WINDOW FRAME

FLASHING INSTALLED AS DETAIL A093

1" TO SUIT WINDOW FRAME

WINDOW SILL AND CASING (BY OTHERS)

- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.  
1 Regalcrest Court,  
Woodbridge, Ontario, Canada L4L 8P3  
Tel: 905-652-0001 Fax: 905-652-0002  
Toll Free: 1-877-747-9255  
Web Page: www.nuformdirect.com

8" CF8i WALL -  
HOLLOW METAL WINDOW



DRAWING NO.

A225

COPYRIGHT 2008

SCALE:

2":1'

REVISION No.:

R00