



## HEADER SECTION



## OPENING



(14)

APPLY 6mm CORNER BEAD OF SEALANT AT TOP OF STARTER TO FLASHING AT HEADER OF OPENING.

## JAMB SECTION


UNCORED CONFORM STARTER INSTALLED AS DETAIL A090

(15)


INSTALL SHIMS TO CENTRE DOOR FRAME IN ROUGH OPENING

(16)

FASTEN FRAME WITH 9.5φx127 FLATHEAD EXPANSION ANCHOR BOLTS. (3 PER JAMB)



## SILL SECTION



- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.  
1 Regalcrest Court,  
Woodbridge, Ontario, Canada L4L 8P3  
Tel: 905-652-0001 Fax: 905-652-0002  
Toll Free: 1-877-747-9255  
Web Page: www.nuformdirect.com

150mm CF6 WALL-  
HOLLOW METAL DOOR  
EXTERIOR



DRAWING NO.

A122

COPYRIGHT 2008

SCALE:

1:5

REVISION No.:

R00