

HEADER SECTION

150mm CF6 WALL

NO CAULKING ABOVE
AND AT ENDS OF
HEADER FRAME

PREFABRICATED
16x25mm NOTCH IN
ALL HEADER

ALUMINUM HEADER

PREFABRICATED
15mm HIGH x 80mm LONG
NOTCH IN BOX
CONNECTOR AT EACH
END OF HEADER

HORIZONTAL REINFORCING
BARS AS REQUIRED

BOLTED CONNECTION
JAMB TO HEADER

OVERHEAD DOOR
(BY OTHERS)

JAMB SECTION - TOP

JAMB SECTION - BOTTOM

SILL SECTION

ALUMINUM JAMB

SLOPED SILL
AT DOOR

ALUMINUM JAMB

2 - 50x50x6.4 FOOT BRACKETS
BY 64mm LONG ANCHORED TO
FOUNDATION

2 - 16 ϕ x102 STAINLESS STEEL
EXPANSION ANCHORS
(BY OTHERS)

- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST
BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL
ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.
1 Regalcrest Court,
Woodbridge, Ontario, Canada L4L 8P3
Tel: 905-652-0001 Fax: 905-652-0002
Toll Free: 1-877-747-9255
Web Page: www.nuformdirect.com

150mm CF6 WALL-
OVERHEAD DOOR -
ALUMINUM FRAME



DRAWING NO.

A152

COPYRIGHT 2008

SCALE:

1:5

REVISION No.:

R00