

12mm ($\frac{1}{2}$ ") GYPSUM BOARD WITH TYPE S-12 x25mm (1") STEEL SCREWS AT 305 O/C. PROVIDE 2 COATS OF JOINT COMPOUND TO SCREW HEADS AND TAPED JOINT

89mm ($3\frac{1}{2}$ ") GALVANIZED 20 GA STEEL STUDS AT 610mm O/C, SELF SUPPORTING AND ATTACHED TO FLOOR AND CEILING RUNNERS, IN ACCORDANCE WITH AISI SPECIFICATIONS.

50mm POLYURETHANE INSULATION WITHIN CF8i FORMS

150mm CONCRETE WALL WITHIN CF8i FORMS.

INTERIOR

EXTERIOR

100 200

PLAN VIEW

- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.
1 Regalcrest Court,
Woodbridge, Ontario, Canada L4L 8P3
Tel: 905-652-0001 Fax: 905-652-0002
Toll Free: 1-877-747-9255
Web Page: www.nuformdirect.com

200mm CF8i WALL -
GYPSUM WALL BOARD
(THERMAL BARRIER)



DRAWING NO.

A315

COPYRIGHT 2008

SCALE:

1:7.5

REVISION No.:

R00