

HEADER SECTION

150mm CF6 WALL

NO SEALANT ABOVE FLASHING

FLASHING INSTALLED AS DETAIL A092

25 40
150

17
APPLY SEALANT WITH BACKING ROD ALL AROUND AT EACH SIDE OF WINDOW FRAME

WINDOW (BY OTHERS)

OPENING

14

APPLY 6mm CORNER BEAD OF SEALANT AT TOP AND BOTTOM OF STARTER TO FLASHING AT HEADER AND SILL OF OPENING.

JAMB SECTION

UNCORED CONFORM STARTER INSTALLED AS DETAIL A091

15

ANCHOR WINDOW AS REQUIRED BY WINDOW MANUFACTURER

SILL SECTION

WINDOW (BY OTHERS)

17
APPLY SEALANT WITH BACKING ROD ALL AROUND AT EACH SIDE OF WINDOW FRAME

FLASHING INSTALLED AS DETAIL A093

25
TO SUIT WINDOW FRAME

WINDOW SILL AND CASING (BY OTHERS)

- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.
1 Regalcrest Court,
Woodbridge, Ontario, Canada L4L 8P3
Tel: 905-652-0001 Fax: 905-652-0002
Toll Free: 1-877-747-9255
Web Page: www.nuformdirect.com

150mm CF6 WALL -
HOLLOW METAL WINDOW



DRAWING NO.

A222

COPYRIGHT 2008

SCALE:

1:5

REVISION No.:

R00