

6

APPLY 10 mm CONTINUOUS CORNER BEAD $\frac{10}{+5}$ OF SEALANT AND 10mm CONTINUOUS FLAT BEAD $\frac{10}{+5}$ OF SEALANT ON TOP OF FLASHING AT INSIDE FACE OF FLASHING.

FLASHING
N.T.S.

5

10 mm CONTINUOUS FLAT BEAD OF SEALANT ON TOP OF $\frac{10}{+5}$ FLASHING AND ON INSIDE LEG OF FLASHING, AT EACH END OF FLASHING.

7

APPLY 10 mm FLAT BEAD OF SEALANT AROUND PRE-DRILLED HOLES FOR SCREWS.

CONCRETE WALL WITH CONFORM.

HEADER SECTION

DO NOT APPLY SEALANT ABOVE FLASHING.

16 GA GALVANIZED FLASHING WITH PREDRILLED HOLES FOR SCREWS AT CENTERLINE OF CONCRETE.

8


SECURE FLASHING WITH FLAT HEAD CONCRETE SCREWS AT 50 mm FROM EACH END AND 333 mm o/c MAX.

7

SEALANT AROUND HOLES FOR SCREWS.

6

CONTINUOUS CORNER AND FLAT BEADS OF SEALANT AT TOP OF FLASHING AT INSIDE FACE OF HEADER.



- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.
1 Regalcrest Court,
Woodbridge, Ontario, Canada L4L 8P3
Tel: 905-652-0001 Fax: 905-652-0002
Toll Free: 1-877-747-9255
Web Page: www.nuformdirect.com

CONFORM WALL OPENING
HEADER FLASHING



DRAWING NO.

A092

COPYRIGHT 2008

SCALE:

1:2.5

REVISION No.:

R00