



13mm [1/2"] WALLBOARD
EXTENDED TO GARAGE
SLAB TO COVER CF8i
INSULATION

50mm [2"] RIGID INSULATION

DOUBLE JOIST

38mm [2"]x184mm [8"] SILL
PLATE WITH 12.7mm [1/2"]φ
ANCHOR BOLTS AS REQUIRED

6 mil POLY SHEET FOR
DAMPPROOFING BETWEEN
SILL PLATE AND CONCRETE
(LAP 150mm [6"] WITH AIR AND
VAPOUR BARRIER)

GARAGE SLAB

200mm [7 7/8"]

FACE OF 38mm [2"]x140mm [6"]
STUDS FLUSH WITH FACE OF
CONFORM WALL

INTERIOR FINISH

AIR AND VAPOUR
BARRIER

FLOOR FINISH

FLOOR SHEATHING

WOOD JOIST

NOTCH 40mm [1 1/2"]x
40mm [1 1/2"] AT
ELECTRICAL RACEWAYS

CEILING FINISH

TRIM

VERTICAL REINFORCING BARS.
SEE PLANS FOR LOCATION

40mm [1 1/2"]

200mm [8"] CF8i WALL

- DETAIL FOR FORMWORK ONLY
- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST
BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL
ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.
100 Galcat Drive, Unit #2,
Woodbridge, Ontario, Canada L4L 0B9
Tel: 905-652-0001 Fax: 905-652-0002
Toll Free: 1-877-747-9255
Web Page: www.nuformdirect.com

200mm [8"] CF8i WALL - INTERIOR GARAGE WALL



DRAWING NO.		S752	
COPYRIGHT 2024			
SCALE:		REVISION No.:	R00