



HOOK DIMENSIONS

CONFORM WALLS	A	CORING WIDTH	D <sub>MAX</sub> (PIN DIA)	
			10M(#4)	15M(#5)
CF4	150mm [6"]	63mm [2 1/2"]	45mm [1 3/4"] <sup>(1)</sup>	N/A
CF6	200mm [8"]	110mm [4 3/8"]	60mm [3"]	65mm [2 1/2"] <sup>(1)</sup>
CF8	250mm [10"]	150mm [5 7/8"]	60mm [3"]	90mm [4 3/4"]
CF8i	200mm [8"]	110mm [4 3/8"]	60mm [3"]	65mm [2 1/2"] <sup>(1)</sup>

- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL ENGINEER AND / OR PROJECT ARCHITECT.

- USE STANDARD PIN DIAMETER 6db, EXCEPT USE PIN DIAMETER FOR STIRRUPS AND TIES, 4db, AS NOTED (1)



Nuform Building Technologies Inc.  
 100 Galcat Drive, Unit #2,  
 Woodbridge, Ontario, Canada L4L 0B9  
 Tel: 905-652-0001 Fax: 905-652-0002  
 Toll Free: 1-877-747-9255  
 Web Page: www.nuformdirect.com

## CONFORM WALL - CORNER REINFORCEMENT



DRAWING NO.	T051
COPYRIGHT 2024	

SCALE:	REVISION No.: R00
--------	-------------------