



CAP FLASHING & WOOD BLOCKING (BY OTHERS)

TO SUIT

200mm [8"] CF8i WALL

25mm [1"] CLEAR

38mm [1 1/2"] x 38mm [1 1/2"] x 76mm [3"]  
EMBEDDED PLASTIC NAILING INSERTS  
ALTERNATING AT INSIDE AND  
OUTSIDE FACE AT 667mm [2'-2 1/4"] O/C  
(EVERY SECOND PANEL)

FACE OF ANGLE TO BE LEVEL  
AND PLUMB WITH GIRT ANGLE  
AND FOUNDATION ANGLE

6.4mm [1/4"] φ x 76mm [3"]  
FLANGED HEX HEAD  
SCREWS AT 200mm [8"] O/C.

ROOFING MEMBRANE  
CONTINUOUS TO UNDERSIDE  
OF CAP FLASHING

CONTINUOUS FIELD WELDED 127mm [5"] x 89mm [3 1/2"] x  
6.4mm [1/4"] ANGLE (MIN.) WITH 7.9mm [5/16"] x 40mm [1 1/2"]  
VERTICALLY SLOTTED HOLES AT 200mm [8"] O/C. SEE  
DETAIL 'A' (BY OTHERS)

INSULATION & ROOFING  
(BY OTHERS)

STEEL DECK &  
JOIST (BY OTHERS)

FIELD WELD

STEEL BEAM & COLUMN  
BEYOND (BY OTHERS)

- DETAIL FOR FORMWORK ONLY

- ALL DETAILS, REINFORCING STEEL & CONCRETE MUST  
BE DESIGNED & CONFIRMED BY PROJECT STRUCTURAL  
ENGINEER AND / OR PROJECT ARCHITECT.



Nuform Building Technologies Inc.  
100 Galcat Drive, Unit #2,  
Woodbridge, Ontario, Canada L4L 0B9  
Tel: 905-652-0001 Fax: 905-652-0002  
Toll Free: 1-877-747-9255  
Web Page: www.nuformdirect.com

## 200mm [8"] CF8i WALL - ROOF CONNECTION



DRAWING NO.		<b>T832</b>	
COPYRIGHT 2024			
SCALE:	REVISION No.:		
	<b>R00</b>		